

PRODUCT NAME: 8668 DITCH WITCH BUFF TOUCH UP
 PRODUCT CODE: H8668

HMIS CODES: H F R P
 1 2 0 B

=====
 SECTION I - MANUFACTURER IDENTIFICATION
 =====

MANUFACTURER'S NAME: H-I-S PAINT MANUFACTURING COMPANY INC
 ADDRESS : 1801 WEST RENO
 OKLAHOMA CITY, OKLAHOMA 73106-3217
 EMERGENCY PHONE : 405-232-2077 DATE PRINTED : 6/1/04
 INFORMATION PHONE : 405-232-2077 REVISION DATE : 02/02/04
 24 HOUR EMERGENCY : 405-640-5304 NAME OF PREPARER : STEVE BUSSJAEGER
 24HR EMERGENCY(ALT) : 405-376-9327, 405-692-7269, or 405-691-0479

=====
 SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION
 =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @	TEMP	PERCENT
MINERAL SPIRITS (ALIPHATIC PETROLEUM DISTILLATES)	8052-41-3	1.7	68°F	30-40%
ACGIH TLV: 100 PPM				
OSHA PEL: 100 PPM				
H-I-S: 525 mg/m3 (RECOMMENDED)				
LD50: ORAL: > 25ml/kg (RAT) DERMAL: >4 ml/kg (RABBIT)				
LD50: INHALATION: >700 PPM/4 HR (RAT)/LD50's BASED ON SIMILAR PRODUCT				
TITANIUM DIOXIDE	13463-67-7			5-10%
ACGIH TLV: 10 mg/m3 (TWA) TOTAL DUST				
OSHA PEL: 15 mg/m3 (TWA) TOTAL DUST				
VM&P NAPHTHA	64742-89-8	6.5	68°F	<5%
ACGIH TLV: TWA 300 PPM, STEL 400 PPM				
OSHA PEL: 300 PPM				
H-I-S: 1370 mg/m3				
LD50: ORAL: >5 g/kg (RAT); DERMAL: >3g/kg (RABBIT)				
HYDRATED IRON OXIDE	51274-00-1			<5%
ACGIH TLV: 5 mg/m3 (TWA) FUME				
OSHA PEL: 10 PPM (STEL) FUME				
* XYLENE (XYLOL) {o-,m-, p-isomers}	1330-20-7	6.6	68°F	1.2
ACGIH TLV: TWA 100 PPM, STEL 150 PPM				
OSHA PEL: TWA 100 PPM, STEL 150 PPM				
H-I-S: TWA 435 mg/m3, STEL 655 mg/m3				
LD50: ORAL: 4,000 mg/kg (RATS); VAPORS: 5,000 PPM (MICE)				

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
 This material contains ingredients covered by the California "Safe Drinking Water and Toxic Enforcement Act of 1986."
 All components of this product are present on the United States Toxic Substances Control Act (TSCA) chemical substances inventory.

=====
 SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
 =====

BOILING RANGE: 245°F - 307°F SPECIFIC GRAVITY (H2O=1): 1.01
 VAPOR DENSITY: Heavier than air WEIGHT PER GALLON: 8.39 lb/gl
 COATING V.O.C.: 3.16 lb/gl MATERIAL V.O.C.: 3.16 lb/gl
 COATING V.O.C.: 379 g/l MATERIAL V.O.C.: 379 g/l
 EVAPORATION RATE: Slower than ether
 SOLUBILITY IN WATER: Material is not water soluble and/or dispersable in water
 APPEARANCE AND ODOR: Liquid, aliphatic odor

=====
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
=====**FLASH POINT:**

Between 100 and 200°F

EXTINGUISHING MEDIA:

Foam, CO2, dry chemical.

SPECIAL FIREFIGHTING PROCEDURES

Full protective equipment and self-contained breathing apparatus should be used. Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion from heating.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Handle as ignitable liquid. Keep containers tightly closed and isolate from heat, electrical equipment, sparks or flame. Vapors form an explosive mixture in air between the upper and lower explosive limits. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

=====
SECTION V - REACTIVITY DATA
=====**STABILITY:**

Stable

CONDITIONS TO AVOID

Excessive heat, all possible sources of ignition, corrosive atmosphere, poor ventilation, excessive aging.

INCOMPATIBILITY (MATERIALS TO AVOID)

Alkaline materials, strong acids and oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION:

Will not occur under normal conditions.

=====
SECTION VI - HEALTH HAZARD DATA
=====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Solvent vapor or mist can cause dizziness, breathing difficulty, headaches, irritation to nose and throat, loss of coordination. Continued over-exposure can lead to central nervous system depression.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin contact: Can cause irritation. Can cause defatting of skin which can lead to dermatitis. Eye contact: Liquid or vapor can cause irritation, tearing, discomfort, redness and blurred vision.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Liquid can be absorbed through skin causing irritation, defatting and dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause mouth, throat, esophagus and stomach irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

CARCINOGENICITY: NTP **CARCINOGEN:** N/A **IARC MONOGRAPHS:** N/A **OSHA LISTED:** N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation- Move person to fresh air. Eye contact- Flush immediately with a large amount of water for at least 15 minutes and get medical attention. Skin contact- Wash thoroughly with soap and water while removing contaminated clothing and shoes. Ingestion- Do not induce vomiting! Contact physician or your local poison control center immediately.

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all sources of ignition (flames, hot surfaces, and electrical, static, or frictional sparks). Avoid breathing vapors. Ventilate area. Contain and remove with inert absorbent and non-sparking tools. Keep out of sewers.

WASTE DISPOSAL METHOD

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state, and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from excessive heat, sparks or open flames. Keep containers closed when not in use. Store in cool, well ventilated approved areas. Avoid free fall of liquid in excess of a few inches and ground container when pouring. Use non-sparking utensils when handling this material. Keep containers closed and upright when not in use.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. Store large quantities in buildings designed to comply with OSHA 1910.106. Emptied containers may retain hazardous residue and explosive vapors. Keep away from heat, sparks and flames. Do not cut, puncture or weld on or near emptied containers. Wash hands after using and before smoking or eating. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed. **KEEP OUT OF THE REACH OF CHILDREN.**

===== **SECTION VIII - CONTROL MEASURES** =====

RESPIRATORY PROTECTION

Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during the use of this product until vapor and mists levels are below applicable exposure limits. Observe OSHA Standard 29CFR1910.134.

VENTILATION

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Refer to OSHA Standard 29CFR1910.94.

PROTECTIVE GLOVES

Use chemical/solvent impermeable gloves to avoid contact with product.

EYE PROTECTION

Avoid contact with eyes. Use safety eyewear with splash guards or side shields, chemical goggles, face shields.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended. Avoid contact

with contaminated clothing. Wash contaminated clothing, including shoes, before reuse.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using washroom, smoke in smoking areas only.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is based on data considered accurate. No warranty expressed or implied is made. H-I-S Paint assumes no responsibility for damage to person, property or business caused by the material. It is the responsibility of the purchaser or user of the material to ensure that it is properly used.