



FEATURES & BENEFITS

VACUUM SYSTEM 3,800 CFM vac system makes sure you have the flow and suction needed to remove massive amounts of material.

REAL-TIME WEIGHT Onboard scale allows you to easily monitor your total truck weight in real-time. The machine will even turn off suction when weight has been hit, ensuring you don't get too heavy.

EASIER OFFLOADING Tiltable debris tank and fully opening door combine for an easy offloading process that requires less manual labor.

FRESH WATER TANK CAPACITY 800-gallon water tank ensures you have the water needed for long days of excavation.

DEBRIS TANK CAPACITY 8 cubic yard debris tank packs the capacity needed to spend more time working and less time offloading.

WATER SYSTEM Single-reel 18.5 GPM water system will keep you working at a productive rate.

W8 HYDRO VACUUM EXCAVATOR

DIMENSIONS

U.S.

Length	31 ft 2 in
Width	8 ft 6 in
Height	10 ft 9 in
Dry weight, estimated	36,400 lbs
GVWR	66,000 lbs

POWER

Engine	Paccar® PX-9
Fuel	Diesel
Manufacturer's gross power rating	370 hp
Transmission	Allison® 3000RDS 6 Speed Automatic
Emissions compliance	EPA Tier 4

VACUUM SYSTEM

Air flow	3,800 cfm
Vacuum, max	27 in Hg
Vacuum tank capacity	8 yd³
Tank outlet valve size	8 in
Filter type	Cyclonic
Suction hose	8 in
Tank tilt angle	36°

WATER SYSTEM

Water pump flow, max	18.5 gpm
Water pump pressure, xax	2,800 psi
Freshwater, dual tanks	400 gal each

ADDITIONAL FEATURES

ADDITIONAL FEATURES					
	Boom reach	26 ft			
	Boom rotation	340°			
	Boiler	Dynablast 420K BTU			
	Heated cabinets				
	Optional Van Air System™	200 cfm @ 150 psi (high)	100 cfm @ 100 psi (low)		

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown. *Stability claim based on lab test of competitive equipment.



